




Introduce

HC-L017

Trays

Order	Quantity	Material	Dimensions(W)x(D)
18 L	Standard 3pcs, Max 5pcs	Aluminum	192x285mm
23 L	Standard 3pcs, Max 5pcs	Aluminum	192x380mm



Technical Parameters

Order Code	Model Number	Type	Power	Chamber Dimensions	Weight
18 L	HC-L017-18-D	Class B	2000W/220V	φ247x350mm	47kgs
23 L	HC-L017-23-D	Class B	2000W/220V	φ247x450mm	53kgs

ICANCLAVE D STERILIZERS



Efficiency

- 1.Full Automatic operating.
- 2.High efficient steam generator.
- 3.High vacuum efficiency.



Safety

- 1.Double safety lock.
- 2.Temperature and pressure overloading protecting.
- 3.Electronic protecting.





Default Program

Program	Temperature	Pressure	Holding Time (min)	Total Time(min)
Solid 134°C	134°C	210kpa	4	17-22 19-24 21-33 22-35
Solid 121°C	121°C	110kpa	20	25-35 25-35 30-40 31-40
Wrapped 134°C	134°C	210kpa	4	22-40 25-40 25-45 30-50
Wrapped 121°C	121°C	110kpa	20	38-50 42-50 45-60 48-60
Textile 134°C	134°C	210kpa	8	25-45 30-45 31-50 36-55
Textile 121°C	121°C	110kpa	30	50-60 52-60 53-70 44-70
Prion 134°C	134°C	210kpa	18	35-55 40-55 40-60 46-65
Liquid 121°C	121°C	110kpa	30	38-50 40-50 43-55 45-60
B&D Test	134°C	210kpa	3.5	10-20 11-23 13-25 16-30
HELIX Test	134°C	210kpa	3.5	10-20 11-23 13-25 16-30
Vacuum Test	/	/	/	17-20 18-21 19-22 20-25

Overall Dimensions

Order Code	Width (W)	Height(H)	Deep(D)
18	490mm	455mm	600mm
23	490mm	455mm	690mm

